

## 650<sup>™</sup> Wide Bagging System

High Speed Bagging  
and Printing System

Wide bag packaging for  
ecommerce order fulfillment,  
short-run and build-on-demand  
applications



## Markets Served



Mail Order and e-commerce Fulfillment



Prescription-by-mail Fulfillment



Catalog Order Fulfillment



Spare Parts Distribution



Short-run production with frequent changeovers in any market



69.5 in. Length x 41.6 in. (Adjustable) Width

37.1 to 47.1 in.

## FEATURES AND BENEFITS

- Capable of cycling at speeds up to 40 bags per minute
- 16" wide bag loading area is ideal for large or bulk products
- Next-bag-out printing is achieved with a thermal transfer imprinter positioned directly over the next large bag to be loaded which prevents product queuing, and eliminates a separate labeling operation
- Adjustable pass-through up to 6" for maximum flexibility and packaging efficiency
- Can be networked to facilitate full pack station integration and central monitoring
- Easily integrates with most Warehouse Management System (WMS) products for e-commerce fulfillment applications
- Inherently safe, configurable for left or right-hand access to the HMI, cycle switch, and bag loading area, improving ergonomics and operator productivity
- System matched AUTOBAG brand bags-on-a-roll and AutoLabel Thermal Transfer Ribbon
- Service & support
- Custom engineering & integration

## Technical Information

### WEIGHT

450 lbs.\*

### ELECTRICAL

Universal Input:

110V to 240V VAC, 50/60 Hz.

Power Consumption: 600 Watts (VA) max

### AIR FEED

5 CFM/80 psi of clean, dry air

### PASS-THROUGH

6 in. Max

### BAG THICKNESS

1.09 – 4.0 mil

### BAG SIZES

W 4 to 16 in. L 5.5 to 27 in.  
(36 in L unsupported)

### WEIGHT CAPACITY

Up to 5 lbs. (with load shelf)

\*For standard configuration only.