600™ Wide Bagging System

High Speed Bagging and Printing System

Designed to bring flexibility, reliability, and high productivity to large bag packaging applications





Markets Served



Aerospace & Defense



Apparel & Accessory Packaging



Automotive



Electronics



Hardware & Fasteners



Healthcare



Hobby & Craft



Household Products



Personal Products



Pet Products



Toys









69.5 in. Length x 41.6 in. (Adjustable) Width

FEATURES AND BENEFITS

- Capable of cycling at speeds over 65 bags per minute
- 16" wide bag loading area is ideal for large or bulk products
- Inherently safe, configurable for left or right-hand access to the HMI, cycle switch, and bag loading area, improving ergonomics and operator productivity
- Adjustable pass-through up to 6" for maximum flexibility and packaging efficiency
- Easily integrates with inline printers, counters, scales, and conveyors for semi- to fully-automatic bagging
- Can also be networked to facilitate full pack station integration and central monitoring
- A complete Print-and-Pack[™] station is achieved when integrated with the AutoLabel 600P[™] inline imprinter
- System matched AUTOBAG brand bags-on-a-roll, AutoLabel Thermal Transfer Ribbon, and Autolabel Design Software
- Service & support
- Custom engineering & integration

Technical Information

WEIGHT

410 lbs.

ELECTRICAL

Universal Input: 110V to 240V VAC, 50/60 Hz. Power Consumption: 500 Watts (VA) max

AIR FEED

5 CFM/80 psi of clean, dry air

PASS THROUGH

6 in. max

BAG THICKNESS

1.09 - 4.0 mil

BAG SIZES

W 4 to 16 in. L 5.5 to 27 in. (36 in. L unsupported)

WEIGHT CAPACITY

Up to 5 lbs. (with load shelf)