

DESCRIPTION

AUTOBAG® Brand Tabletop Bagging Systems efficiently bag and seal your products. Available in two model configurations operating at speeds up to 25 bags per minute (BPM) for the PS 125 and 15 BPM for the PS 125 OneStep. These hand load machines bring simplicity, versatility and value to your low- to mid-volume production environment.

These tabletop baggers are simple to operate and offer innovative engineering in a straightforward, compact design. Equipped with a user-friendly display that enables easy access to operating parameters, job set-up, job storage, and on-board system diagnostics to simplify maintenance and maximize productivity.

The PS 125 OneStep includes the same conveniences of the standard PS 125 with the addition of a built-in imprinter. It features next-bag-out printing technology, making it ideal for short run, order fulfillment, and e-commerce applications.

KEY BENEFITS



Operational Efficiency

- Open load area and controlled seal bar maximize loading flexibility and operator safety
- Locking turntable and AutoThread™ feature provide easy bag access and changeover
- Dedicated service access simplifies maintenance and repairs to minimize downtime
- Easy to navigate menu structure with job storage and recall, as well as on-board diagnostics to maximize productivity
- Quiet, all-electric design does not require compressed air to operate
- Compact design is ideal for low to mid-volume packaging operations
- Graphics, text and bar codes can be printed on the bag, eliminating the need for a separate labeling operation*
- Tilt-back printer enables fast and easy maintenance*



Package Optimization

- Engineered to work with AUTOBAG® brand pre-opened bags-on-a-roll, available in a variety of material options for broad application requirements
- Multi-position bag support shelf for added flexibility
- Features next bag-out printing technology, ideal for short run and order fulfillment applications*



* PS125 OneStep Feature Only

TECHNICAL DATA

	PS125	PS125 OneStep
DIMENSIONS: (W x L x H)	18.3" x 23.5" x 21.7" (464.8 mm x 597 mm x 551.2 mm)	21.4" x 23.5" x 26.6" (543.6 mm x 597 mm x 675.6 mm)
WEIGHT:	90 lbs.	120 lbs.
SPEED:	Up to 25 BPM	Up to 15 BPM
ELECTRICAL:	100-240V, 50/60 Hz	100-240V, 50/60 Hz
CONNECTIVITY:	N/A	Ethernet, USB, and Serial
BAG SIZES: (W x L)	2" - 10.5" x 4" - 17" (50.8 mm - 266.7 mm) x (101.6 mm - 431.8 mm)	2" - 10.5" x 4" - 17" (50.8 mm - 266.7 mm) x (101.6 mm - 431.8 mm)
BAG THICKNESS:	1.0 - 4.0 mil	1.0 - 4.0 mil

EQUIPMENT LAYOUT

