

500™

High speed bagging machine

Automatic bag sealing machine designed for reliability, flexibility and optimising packaging throughput







500™

High speed bagging machine

Automatic bag sealing machine designed for reliability, flexibility and optimising packaging throughput



FEATURES AND BENEFITS

- Capable of cycling at speeds up to 100 bags per min.
- Touch screen accesses operator tutorials, help and diagnostics.
- The system can be networked for full pack station integration to facilitate central monitoring and the extraction of productivity information.
- Capable of being configured for left or right-hand access.
- The system features a simple design with very few moving parts, reducing lifetime cost and improving uptime.
- Easily integrates with inline printers, counters, scales, and conveyors for semi to fully automatic bagging.
- Height adjustment and casters for ergonomics and portability.

SPECIFICATIONS Weight 158 kg H: 943 to 1196 mm Overall Size W: 955 mm L: 1639 mm Electrical 110/240 VAC, 50/60 Hz, 500 Watts (VA) max Air Feed 5 CFM/80 psi of clean, dry air Pass-through 125 mm max Bag thickness 35-100 µm Bag widths 55-300 mm 70-550 mm Bag lengths Up to 2.2kg (with load shelf) Weight capacity

TYPICAL APPLICATIONS

















SUSTAINABILITY

As a maker of flexible packaging products, we recognise the need for greater awareness and involvement in creating a more sustainable planet – from the point of manufacture to the point of disposal.

For over a decade, we have been producing environmentally responsible products for our customers. We introduced GeoTech®, a line of pre-consumer reprocessed films that forever changed the packaging industry. We have introduced innovative, lighter gauge films that reduce the amount of material required without compromising packaging performance. In addition, our machinery technology continues to evolve with new, state-of-the-art components and engineering designed to reduce energy consumption.

