

PS 125[™]

Tabletop bagging machine

Designed to bring simplicity, versatility and quality to hand load packaging applications







PS 125[™]

Tabletop bagging machine

Designed to bring simplicity, versatility and quality to hand load packaging applications



FEATURES AND BENEFITS

- Operating at speeds up to 25 bags per minute, it offers innovative engineering in a straightforward, tabletop design.
- Operator-friendly control screen for quick and easy job storage.
- Easily change bag sizes in less than 2 minutes.
- All-electric system: does not require compressed air.
- Open loading area and controlled seal bar for maximum loading flexibility and operator safety.
- Automatic or manual operating modes for optimum productivity.

SPECIFICATIONS	
Weight	37 kg
	H: 560 mm

W- 560 mm

Overall Size

Overall Oize	W. 500 Hilli
	D: 480 mm
Electrical	110/240 VAC, 50/60 Hz, 5.0/2.7 Amps
Pass-through	86 mm
Bag thickness	35-100 μm
Bag widths	55-260 mm
Bag lengths	102-430 mm

TYPICAL APPLICATIONS















SUSTAINABILITY

As a maker of flexible packaging products, we recognise the need for greater awareness and involvement in creating a more sustainable planet – from the point of manufacture to the point of disposal.

For over a decade, we have been producing environmentally responsible products for our customers. We introduced GeoTech®, a line of pre-consumer reprocessed films that forever changed the packaging industry. We have introduced innovative, lighter gauge films that reduce the amount of material required without compromising packaging performance. In addition, our machinery technology continues to evolve with new, state-of-the-art components and engineering designed to reduce energy consumption.

