

# Opaque, Mail Bag Film - MB



## **BENEFITS**

This three layer co-extruded film is a blend of linear low density and low density polyethylene.

The Opaque Film is specifically engineered for order fulfilment applications.

The film is ideal for direct thermal transfer printing, removing the need to apply adhesive paper shipping labels, therefore retaining full recyclability of the material. The opaque composition offers pricacy for mail order applications.

Standard widths for large mail bags are 400, 475 and 550mm.

This material is black on the inside, white on the outside and can be pre-printed in up to 8 colours.

Optional matt finish material available.

Store in a dry area, temperature should be between 10-30°C. Not to be stored in direct sunlight.

> Hanger Hole - Standard euroslot

- Triangular euroslot - Hanger hole



Recycle Ready\*

### **OPTIONAL FEATURES**

- Carry Handle
- Air Relief Hole
  - Full
  - Perforated
  - Butterfly
- Easy Open Perforation
  - Vertical
  - Horizontal











TESTIMO (E SI ESII ISI MISING	
Compliance	ISO 9001:2015; ISO 14001:2015; BRC
Flexographic printing	Yes
In-line printing	Yes
Trim seal	Yes*
Bag thickness	35, 50, 75 and 100 µm
System compatibility	Autobag; SidePouch

TECHNICAL SPECIFICATIONS

<sup>\*</sup>Subject to machine type





\*Degree of recyclability will vary depending on scope and availability of flexible film collection, sortation and recycling programs.